

MIDNITE SOLAR'S NEW

DIY Series

MPPT INVERTER/CHARGERS

MidNite Solar's new DIY Series Inverter Charger with MPPT represents a versatile line of inverters/chargers at a great price!

MN3024DIY and MN3548DIY!

The MN3024DIY is a 3,000W, 24VDC inverter-charger that includes a built-in MPPT charge controller. The MN3548DIY is a 3,500W, 48VDC inverter-charger with built-in MPPT charge controller. Offering a simple, all-in-one installation and flexible programming, the new MidNite Solar Inverter/charger DIY Series will charge virtually any battery chemistry.

With excellent surge capability, the DIY Series will start the most demanding 120VAC loads. Perfect for your off-grid cabin or house, the DIY Series is designed to be affordable, dependable, and supported by the industry's best customer service personnel at MidNite Solar.



www.midnitesolar.com

19115 62nd Ave. NE., Arlington, WA. 360-403-7207 FAX: 360-691-6862

MIDNITE SOLAR'S NEW
DIY Series
 MPPT INVERTER/CHARGERS



APPLICATIONS:

Off grid - battery and PV or generator required
 Grid connected for backup - battery required

SPECIFICATIONS	MN3024DIY	MN3548DIY
System Voltage	24VDC	48VDC
AC		
Max Rated Power	3000W	3500W
Surge Power	6000W	7000W
Power Factor	1	1
Input Voltage	120VAC	120VAC
Input Voltage Range	85-140VAC +- 2% Adjustable	85-140VAC +- 2% Adjustable
Input/Output Frequency	60Hz	60Hz
Output Voltage	120VAC +- 5%	120VAC +- 5%
Output Waveform	Pure Sine Wave	Pure Sine Wave
Peak Efficiency	>95%	>95%
Max AC Charging Current	40A	30A
Internal Bypass Current	Up to 40A	Up to 40A
Conversion (Bypass and Invert)	10ms	10ms
SOLAR CHARGER		
Max PV Input/Output Power	1600W	4400W
Max PV Charging Current	60A	80A
Max PV Input Voltage	100V	145V
Algorithm	MPPT	MPPT
MPPT Voltage Range	30 -85V	60 - 115V
BATTERY CHARGER		
Battery Type	Lead Acid or Lithium	Lead Acid or Lithium
Max Battery Charging Current	80A (Adjustable)	120A (Adjustable)
Battery Voltage Range	20 - 33V DC	40 - 60V DC
Nominal Battery Voltage	24V	48V
ENVIRONMENTAL/MECHANICAL/WARRANTY		
Size	14.90"L x 11.03"W x 4.06"H	16.93"L x 13.31"W x 4.96"H
Operating Temperature	5°F ~ 131°F / -15°C ~ 55°C	5°F ~ 131°F / -15°C ~ 55°C
Storage Temperature	-13°F ~ 140°F / -25°C ~ 60°C	-13°F ~ 140°F / -25°C ~ 60°C
Humidity	5% ~ 95% (3 Layer Paint Protection)	5% ~ 95% (3 Layer Paint Protection)
Warranty	1 Year	1 Year

Manufactured for MidNite Solar in China.

